

# BALL JOINTS APPLICATION ANALYSES FORM



ESZ Makina İnş. San. Ve Dış Tic. Ltd. Şti.  
Perpa Tic. Merk. A Blok K:11 No:1354 İstanbul – Türkiye  
Tel: + 90 (212) 210 52 07 – 08  
Fax: +90 (212) 210 52 09  
Email: info@eszmakina.com  
Web: www.eszmakina.com

Document No. : FR 7 25 E  
Release Date : 02.03.2014  
Rev. No. : 00

Company Name: \_\_\_\_\_ Date: \_\_\_\_\_

Address: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Tel: \_\_\_\_\_ Fax: \_\_\_\_\_

Contact: \_\_\_\_\_ Email: \_\_\_\_\_

Information about application, if possible please send us drawing

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Quantity: \_\_\_\_\_ pcs Medium: \_\_\_\_\_

Size: \_\_\_\_\_ or Nominal Size: \_\_\_\_\_ or Flow Rate: \_\_\_\_\_

Pressure: \_\_\_\_\_ Bar \_\_\_\_\_ psi

Temperature: \_\_\_\_\_ °C \_\_\_\_\_ °F

Does temperature and pressure change during operation? If yes, please give min. and max. and describe

\_\_\_\_\_  
\_\_\_\_\_

If other brand is used; Brand Name: \_\_\_\_\_ Model: \_\_\_\_\_

Any problems? \_\_\_\_\_

What is the preferred construction material: \_\_\_\_\_

- Seal Type:  Pffe  Grafit Filled Teflon  Bronze Filled Teflon  Glass Filled Teflon  
 Mineral Compound with Inj. Graphite Sealant  
 Ductile Iron with Inj. Graphite Sealant  
 Aluminium Bronze with Inj. Graphite Sealant

Ball Joint Styles:

Style 20



Style 30



Style 30A



Style 40



