ROTARY JOINTS APPLICATION ANALYSES FORM



ESZ Makina İnş. San. Ve Dış Tic. Ltd. Şti. Perpa Tic. Merk. A Blok K:11 No:1354 İstanbul – Türkiye Tel: + 90 (212) 210 52 07 – 08

Tel: + 90 (212) 210 52 07 – 08 Fax: +90 (212) 210 52 09 Email: info@eszmakina.com Web: www.eszmakina.com Document No. : FR 7 31 EN Release Date : 19.06.2015

Rev. No. : 00

Company Name:			Date:
	Fax: _		
	Email: _		_
Information about applic	cation, if possible please send	l us drawing	
Quantity:	pcs		
Size:			
	Threaded Shaft	Flanged Shaft	
If Threaded Shaft; Size:	7	Γhread Type: ☐ NPT [☐ BSP ☐ BSPP ☐ UNF ☐ METRIC
		Direction: ☐ Right I	
Pressure:	Bar	psi	
Temperature:	°С	°F	
Does temperature and pr	ressure change during operat	tion? If yes, please give	min. and max. and describe
	RPM (min ⁻¹) Cyli		
	Steam 🗆 Hot Oil 🗀 Hydra		Other:
Flow Type: Single Flow	v □		
	☐ Siphon Size: an	d Type: Stationary	Siphon
			Thread Type:
		☐ Tube	Timeau Type
		_	
Multiport	Number of ports:	Port Size:	_
For rod supported joints	; Rod spacing: Rod	Diameter:	
How many are being use	d now?	Potential Usage	:
☐ If other brand is used; Brand Name: Model:			
Any problems?			
			_

If you have any questions or need assistance, please contact our sales department. Please fill the form and send it by fax or email.